



# ELEVATION SERIES CUBE ICE MAKER CIM1126

**Ice-O-Matic**  
Ice. Pure and Simple

## Model:

□ CIM1126



CIM1126 ON B42

## Features and Benefits

- 22.25" (565 mm) wide space-saving design.
- Produces up to 968 lbs (439 kg) of ice per day.
- **Energy and Environment**
  - Exceeds new 2018 DOE (Department of Energy) regulations.
  - Up to 20% more energy efficient than other models.
  - Environmentally friendly, including BPA-free plastic and recyclable parts.
- **Sanitation**
  - Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
  - Built in Agion® ensures unbeatable antimicrobial protection.
  - Smart LED light indicates machine status and when cleaning is required.
  - Simple, one-touch controls for sanitization and descaling.
  - BPA-free snap-in, snap-out dishwasher-safe components.
- **Universal Smart Harness™** control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

CIM1126 CUBE ICE MAKER

## Ice Form

FULL CUBE DIMENSIONS	
W x D x H (in.)	7 7/8 x 7 7/8 x 7 7/8
W x D x H (mm)	22 x 22 x 22
HALF CUBE DIMENSIONS	
W x D x H (in.)	3 7/8 x 7 7/8 x 7 7/8
W x D x H (mm)	10 x 22 x 22



CUBE

## Bin Chart Kits for Combining Wider Bins with Smaller Models

ICE STORAGE BINS										
Model No.	B25	B40	B42	B55	B700	B110	B1000	B1300	B1325	B1660
Capacity	242 lbs (110 kg)	344 lbs (156 kg)	351 lbs (160 kg)	510 lbs (232 kg)	680 lbs (308 kg)	854 lbs (388 kg)	1,000 lbs (454 kg)	1,320 lbs (599 kg)	1,325 lbs (601 kg)	1,660 lbs (753 kg)
Width	30 in (762 mm)	30 in (762 mm)	22 in (559 mm)	30 in (762 mm)	30 in (762 mm)	48 in (1,219 mm)	48 in (1,219 mm)	48 in (1,219 mm)	60 in (1,524 mm)	60 in (1,524 mm)
Kits	KBT19		Kit Not Required	KBT19		N/A	Hold Down Securement Recommended			
CIM1126	KBT19		Kit Not Required	KBT19		N/A	Hold Down Securement Recommended			

\*See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

## Options & Accessories

WATER FILTERS		
Ice Machine Model	Manifold	
	System	Replacement
CIM1126	IFQ1	IOMQ (1)

Note: All modular cube CIM units can be installed with the O<sub>3</sub>-Matic™ Ozone Delivery System.

## Ice Maker Warranty


COMMERCIAL WARRANTY	
Ice Maker	3 YEARS parts and labor
Evaporator and Compressor	5 YEARS parts
Evaporator (when enrolled in our filter program)	7 YEARS parts and labor



# CIM126 CUBE ICE MAKER

## Remote Cooled

- A. Ice maker potable water in,  $\frac{3}{8}$ " FPT.
- B. Ice maker water out,  $\frac{3}{4}$ " FPT.
- C. Hole for electrical connections,  $\frac{7}{8}$ ".
- D. Electrical connection junction box,  $\frac{7}{8}$ " (remote).
- E. Condenser water in,  $\frac{3}{8}$ " FPT (water only).  
Discharge line,  $\frac{1}{2}$ " male quick connect coupling  
for precharged line set (remote only).
- F. Condenser water out,  $\frac{1}{2}$ " FPT (water only).
- G. Liquid line,  $\frac{3}{8}$ " male quick connect for  
precharged line set (remote only).



## Operating Requirements

	MINIMUM	MAXIMUM	
		60 Hz	50Hz
Ambient Temp. Range Air	50°F (10°C)	100 °F (38 °C)	110 °F (43 °C)
Water Temp.	40°F (4.4°C)		
Water Pressure	20 PSIG (1.4 BAR)	80 PSIG (5.5 BAR)	

## Dimensions

ALL MODELS	
W x D x H (in.)	22 x 24.25 x 26.9
W x D x H (mm)	559 x 616 x 683

## Specifications

Model Number	Cond. Unit	Half-Cube Ice Production per 24hrs		Water Usage gallons per 100 lbs of Ice 90°F air/70°F water		kWH Used per 100 lbs of ice @ 90°F air/70°F water	Voltage Characteristics	Min. Circuit Ampacity	Fuse Size	Approx. BTUs per hour
		70°F air/ 50°F water lbs (kg)	90°F air/ 70°F water lbs (kg)	Potable	Condenser					
CIM1126R	Remote	968 (439)	855 (388)	19.0	N/A	4.98	208-230/60/1	12.8	20	18,200

\* Daily ice production based on half cube configuration.

Notes:

Number of Wires:	3 (including ground)
Approx. Shipping Weight lbs (kg):	CIM1126R 215 (98)
Refrigerant Type:	R404A